Selection guide

Surface mounted, also available in kit with bidirectional technology

Toona HS
pages 20/21

Toona, Toonakit BD
pages 44/51

- for leaves up to 3 m
  - 24 Vdc version with magnetic encoder, irreversible, with mechanical stop on opening. Compatible with control units with BlueBUS technology, Solemyo and Opera → **TO4024**
    - **KIT** → **TOONA4024BDKCE**
  - 230 Vac
    - irreversible
      - increased speed
        - with limit switch on opening → **TO4005**
        - with limit switch on opening and closing → **TO4006**
      - cruising speed, with limit switch on opening → **TO4015**
    - reversible, increased speed, with limit switch on opening → **TO4605**
- for leaves up to 5 m
  - 24 Vdc version with magnetic encoder, irreversible, with mechanical stop on opening. Compatible with control units with BlueBUS technology, Solemyo and Opera → **TO5024**
    - Hi-Speed → **TO5024HS**
    - for intensive use → **TO5024I**
  - 230 Vac
    - irreversible, cruising speed
      - with limit switch on opening → **TO5015**
      - with limit switch on opening and closing → **TO5016**
    - reversible, increased speed
      - with limit switch on opening → **TO5605**
- for leaves up to 6 m
  - 24 Vdc version with magnetic encoder, irreversible, with mechanical stop on opening. Compatible with control units with BlueBUS technology, Solemyo and Opera
    - Hi-Speed → **TO6024HS**
- for leaves up to 7 m
  - 24 Vdc version with magnetic encoder, irreversible, with mechanical stop on opening. Compatible with control units with BlueBUS technology, Solemyo and Opera → **TO7024**

Titan HS
pages 24/25

- for leaves up to 3.7 m
  - 24 Vdc, irreversible, increased speed, with magnetic encoder → **TTN3724HS**
  - 24 Vdc, reversible, increased speed, with magnetic encoder → **TTN3724RHS**
- for leaves up to 6 m
  - 24 Vdc, irreversible, increased speed, with magnetic encoder → **TTN6024HS**
  - 24 Vdc, reversible, increased speed, with magnetic encoder → **TTN6024RHS**

Wingo HS
pages 22/23

Wingokit BD
pages 52/59

- for leaves up to 2 m
  - 24 Vdc, irreversible, increased speed. Compatible for operation with Solemyo → **WINGO4024BDKCE**
  - 230 Vac → **WINGO4KIT**
- for leaves up to 3 m
  - 24 Vdc version with magnetic encoder, irreversible, with mechanical stop on opening. Compatible with control units with BlueBUS technology, Solemyo and Opera
    - Hi-Speed → **WG3524HS**
- for leaves up to 3.5 m
  - 24 Vdc, irreversible, increased speed. Compatible for operation with Solemyo → **WINGO5024BDKCE**
  - 230 Vac → **WINGO5BDKCE**